




The modular PPC-5100 GT POS system is specially suited for use in a demanding retail environment. It is extremely powerful and extensively equipped. The system is not only highly integrated; it also provides countless connector ports and is both versatile and expandable. It goes without saying that it highest quality is included. And, as with all 4POS products, there is a life-cycle guarantee of at least 5 years.




## POS PC PPC-5100 GT



1. Small in size but consolidated in design



2. Tool free HDD and ODD access with RAID 0,1 built-in



3. Modular design for easy maintenance



4. Optional powered USB ports



5. Rich I/O connector ports



6. Dual LAN ensures safety of all business transactions



# PPC-5100 GT



Model Name		PPC-5100 GT
<b>Housing</b>		
		Sheet Metal
<b>Mainboard</b>		
		C69
CPU		Intel i5-2400 3.1GHz / i3-2120 3.3GHz / Celeron G540 2.5GHz
Chipset		Intel® PCH Cougar Point Q67 (with RAID)
System Memory		2 x DDR3 Long DIMM slot up to 16GB, FSB 1066/1333 MHz
Graphic Memory		Intel® HD Graphics 2000/3000, Integrated in CPU, frequency 850MHz (dynamic frequency up to 1.1GHz)
<b>Storage</b>		
Device Bay		2x 3.5" SATA HDD
<b>Expansion</b>		
PCI / PCI-E Socket (x16)		Riser card (1 x PCI x1 slot & 1 x PCI-E x16 slot)
<b>Front External I/O Ports</b>		
USB port		2x USB 2.0 (one covered by lid)
<b>Rear External I/O Ports</b>		
USB port		4x USB 2.0
PS2		1
Powered Serial / RS232		5x DB-9 M(COM1/COM2/COM3/COM4/COM5 standard RS-232, 5V/12V selectable by BIOS)
Parallel		1
LAN		1- 2 x RJ45 (10/100/1000MBit)
VGA		1 x D-Sub (15 pin) with Power over VGA (activated via BIOS)
Cash Drawer Port		1 x RJ-11 with 12V or 24V
DisplayPort		1
Audio		1 x Line-out, 1 x Microphone-in
Power Out		24V
<b>Communication</b>		
		half-size miniCARD type (PCI-E), 802.11 a/b/g wireless LAN card & antenna (option)
<b>Power</b>		
Power Supply		Internal ATX 230W power supply
<b>Control / Indicator</b>		
Power Switch		1 (front)
Power Indicator		1 x LED blue
HDD Indicator		1 x LED blue
<b>Communication</b>		
		half-size miniCARD type (PCI-E), 802.11 a/b/g wireless LAN card & antenna (option)
<b>Environment</b>		
EMC & Safety		FCC Class A / CE Mark / LVD
Operating Temperature		5°C ~ 35°C
Operating Humidity		20% - 85% RH non-condensing
<b>Option</b>		
Serial RS422 / 485		1x (COM6), cable type
SATA SSD		5°C ~ 35°C
USB Hub / Powered USB		4 x USB 2.0 + 4 x Powered USB 2.0: 1x 24V, 2x 12V, 1x 5V
SATA ODD		DVD RW
Power Supply		Internal 350W ATX power supply
<b>Dimension (W x D x H)</b>		
		270 x 300 x 120 mm
<b>Weight</b>		
		8 kg
<b>Colour</b>		
		Black
<b>OS Support</b>		
		Windows® XP Professional, Windows POSReady 2009, Windows XP Embedded, Windows XP Professional for Embedded, Windows 7, Linux, POSReady 7

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

